

sidekick

The compact, by-your-side, all-in-one scanner.



Everything you need for desktop document management, all in one box:



Full color duplex scanner



USB Cable included for immediate “plug and play”



Energy efficient



VRS image enhancement, auto cropping and de-skew





Cario scanning application for flawless image capture and processing

Scan to PDF, file, archive, retrieve, publish, e-mail and adjust all of your documents from the desktop with the touch of a button.



sidekick¹²⁰⁰

sidekick¹⁴⁰⁰

Scanning Mode		Duplex			
Scanning Speed Letter Size Portrait	Binary 200 dpi	Simplex 23 ppm (pages per minute) Duplex 42 ipm (images per minute)		Simplex 43 ppm (pages per minute) Duplex 76 ipm (images per minute)	
	Color 150 dpi	Simplex 10 ppm Duplex 18 ipm		Simplex 19 ppm Duplex 34 ipm	
Resolution		100-600 dpi Optical: 600 dpi			
Output Options		Bitonal, Grayscale (8 bit), and Color (24 bit)			
Image Enhancement		 Cropping, Deskew, Brightness and Contrast Control			
Document Size		2.0 x 2.8 in. (50.8 x 70 mm) to 8.5 x 14 in. (216 x 356 mm)			
Paper Thickness		Single Paper Feeding: 20 to 59 mils (0.05 to 0.15 mm) Continuous Paper Feeding: 2.36 to 5.9 mils (0.06 to 0.15 mm) Note: 1 mil = 1/1000 in.			
Paper Weight		Single Paper Feeding: 10.7 to 33.9 lbs. Continuous Paper Feeding: 13.3 to 33.9 lbs.			
Interface		USB 2.0. (cable included), 50 Pin Dual Port SCSI III			
Feeder Capacity		120 Sheets			
Scanner Size		14 x 12.5 x 9.25 in. (35.5 x 32 x 24.1 cm) With Tray Extended: 14 x 19.75 x 10.6 in. (35.5 x 50 x 27 cm)			
Scanner Weight		18.7 lbs (8.5 kg)		20.1 lbs (9.1 kg)	
Power Requirements		AC 100-120 V 50/60 Hz	AC 220-240 V 50/60 Hz	AC 100-120 V 50/60 Hz	AC 220-240 V 50/60 Hz
Power Consumptions	Maximum (Scanning)	37 W	38 W	50 W	50 W
	Minimum (Standby)	17 W	19 W	18 W	19 W
	Sleep Mode	6 W	8 W	6 W	8 W
Environment	Operating Temperature and Humidity	Temperature 59°F to 86°F (15°C to 30°C) Humidity: 30% to 80% RH			
	Storage Temperature and Humidity	Temperature 32°F to 95°F (15°C to 35°C) Humidity: 10% to 80% RH			
Additional Features		End User Replaceable Feeder Rollers Electronic Color Dropout (Red, Green, Blue)			
Additional Contents		Power Cord, USB Cable, Roller Cleaning Paper, CD-ROM (Installation and Operation Manual, VRS, User Utility Software), Printed Documents (Quick Installation Guide and Warranty Card)			
Bundled Software		 Scanning Capture Software			
Consumables Options		Roller Exchange Kit S005503 Roller Cleaning Kit S005504		Roller Exchange Kit S005503 Roller Cleaning Kit S005504 Pre-scan Front-page Imprinter Kit 0123060 Ink Cartridge S005506	

© 2004 Böwe Bell + Howell Scanners, L.L.C. All rights reserved. BÖWE BELL+HOWELL and the Böwe Bell + Howell logo are trademarks or registered trademarks of BBH, Inc. COPISCAN is a registered trademark of Böwe Bell + Howell Scanners, L.L.C. All other trademarks and service marks are the property of their respective owners. Specifications are subject to change without notice.

Phone: 1.800.SCAN.494 or 1.847.675.7600
www.bbhscanners.com Form #SD-193



Böwe Bell + Howell Scanners. Always adding value.